

# LINEUP



## XLR 3P Type

GL-501XLR-2W	L=300mm / cool white color
GL-501XLR-2WY	L=300mm / warm white color
GL-501LXLR-2W	L=450mm / cool white color
GL-501LXLR-2WY	L=450mm / warm white color

## XLR 4P Type

GL-501XLR4-2W	L=300mm / cool white color
GL-501XLR4-2WY	L=300mm / warm white color
GL-501LXLR4-2W	L=450mm / cool white color
GL-501LXLR4-2WY	L=450mm / warm white color

## XLR 3P (L) Type

GL-502XLR-2W	L=420mm / cool white color
GL-502XLR-2WY	L=420mm / warm white color
GL-502LXLR-2W	L=550mm / cool white color
GL-502LXLR-2WY	L=550mm / warm white color

## XLR 4P (L) Type

GL-502XLR-2W	L=420mm / cool white color
GL-502XLR-2WY	L=420mm / warm white color
GL-502LXLR-2W	L=550mm / cool white color
GL-502LXLR-2WY	L=550mm / warm white color




## BNC TYPE

GL-501BNC-2W	L=300mm / cool white color
GL-501BNC-2WY	L=300mm / warm white color
GL-501LBNC-2W	L=450mm / cool white color
GL-501LBNC-2WY	L=450mm / warm white color




## TNC TYPE

GL-501TNC-2W	L=300mm / cool white color
GL-501TNC-2WY	L=300mm / warm white color
GL-501LTNC-2W	L=450mm / cool white color
GL-501LTNC-2WY	L=450mm / warm white color



XLR 3pin



XLR 4pin



BNC

# OPTION

## LED Light designated dimmer switch configuration

GL-510+GL-511

- LED Light designated dimmer switch (GL-510)
- Mounted on Iron Plate (GL-511) and powered by power supply.
- For use on XLR-3pin gooseneck Light.

Dimmer Switch

Material : ABS

Input : DC 12V

Output : DC 12V 100 mA



## LED Light designated dimmer switch

GL-510+GL-510C

- LED Light designated dimmer switch (GL-510)
- Mounted on Clip (GL-511) and powered by PS1 power supply.
- For use on XLR-3pin gooseneck Light.
- Can be clipped on bar 4~30mm diameter



## Power supplier

Input : AC 100 240V 50/60Hz 0.2A

Output : DC 12V 0.5A

Cable length : 1.8M



DH ELECTRONICS

大桓企業股份有限公司

DH ELECTRONICS CO.,LTD.

TEL : +886-6-2800286

FAX : +886-6-2581616

E-mail : vickyhaung@daehuan.com

http://www.daehuan.com